

► Series TRILUB TRE

Three-Screw pump for applications up to 13 bar



► Pumped Liquid

For handling lubricating liquids without any abrasive components in particular lube oils, hydraulic oils and light fuel oils in all industrial fields of application. The pump liquids may not chemically attack the pump material.

► Main Fields Of Application

Oil-fired systems, hydraulic installations, mechanical engineering, general industrial technologies, chemical and petrochemical industries, marine and offshore engineering, lube oil applications

► Performance Data

Capacity	Q	up to	11..130	l/min
Inlet pressure	ps	up to	7	bar
Discharge pressure	pd	up to	16	bar
Differential pressure	pdiff	up to	16	bar
Viscosity	v	up to	2..1500	mm ² /s
Fluid temperature	t	up to	-20..155	°C
Speed	n	up to	3600	1/min

► Construction features

Dry installation
Vertical installation
Horizontal installation
Self - priming
With shaft sealing

Document free of charge by phone +49 7732 86-382 fax +49 7732 86-99382

ALLWEILER GmbH
PO Box 1140
D-78315 Radolfzell Germany
Phone.: +49 (0)7732 86-0
Fax: +49 (0)7732 86-436
E-mail: service@allweiler.de
Internet: <http://www.allweiler.com>